

Preservation  
above-zero

Temperature range

**+2°C to 14°C**

Compact and  
large capacity

New cycle defrosting  
system

**Medical Refrigerators for reliable storage of pharmaceutical and medical supplies**

- Precise temperature control
- Superior cooling performance
- Forced air circulation
- Double-glazing glass door
- Slim, and space saving design
- Useful alarm functions



KM-RS16A1



KM-RS34A1

# KM-RS16A1, KM-RS34A1 Series

## Features

### Improved Energy Saving

Panasonic's new cycle defrosting system achieved 15%\* energy saving compared to conventional models. This system observes the defrosting condition after every cycle, and prevents temperature rises that are caused by defrosting.

\*The data is a measured example (set temp. 5°C, AT 23°C, 230V 50Hz, no load). Actual power consumption will vary depending on the set and ambient conditions, loading and local voltage.

### User Friendly Design

#### 1. New Control Panel

- Newly designed for improved operability, visibility, and calibration
- Digital setup for easy and secure operation
- Temperature alarm settings made on the control panel



#### 2. LED Interior Light

The LED interior light automatically turns on/off in conjunction with the door opening/closing. It can also be controlled from the control panel.



#### 3. Double-Paneled Glass with Heat-Reflective Film

The refrigerator doors constructed of double-paneled glass with heat-reflective film, allow easy loading and unloading of medical supplies while preventing ultraviolet rays, which may damage stored items, from entering the unit. Panasonic's unique heat-reflective film blocks the passage of radiant heat rays through the glass panels and keeps the inside temperature from being adversely affected by excessive amounts of heat.

### Effective Temperature Control

#### 1. Microprocessor Temperature Control

A thermistor sensor monitors temperature inside the chamber, and microprocessor temperature control ensures that the set temperature is maintained. Even if the door is opened and closed frequently, the circulation fan ensures rapid temperature adjustment to provide a highly reliable, stable preservation environment that is not affected by ambient temperature.

#### 2. Fan-Forced Air Circulation

The temperature stays even throughout the inside of the refrigerator with the fan-forced air circulation system. No matter how the load is distributed, every corner of the unit is immediately cooled with no noticeable variation in temperature apparent inside the cabinet.

### Enhanced Alarm and Safety Functions

#### 1. Door Open Alarm

When the door is opened, the Door Open indicator lamp lights automatically. After approx. 2 minutes, a buzzer alarm will sound if the door has not been closed (settable from 0 to 15 minutes). If the door remains open even after the buzzer is stopped, the buzzer rings again after 30 minutes (settable from 0 to 60 minutes in increments of 10 minutes).

#### 2. Abnormal Temperature Alarm

If the inside temperature changes  $\pm 2^{\circ}\text{C}$  to  $\pm 14^{\circ}\text{C}$  from the set temperature, the digital temperature display flashes, and a buzzer sounds an alarm after 15 minutes (settable from 0 to 15 minutes).

## Specifications

	Model No.	
220V-240V, 50Hz	KM-RS16A1E	—
220V, 60Hz	KM-RS16A1K	—
220V, 60Hz (for Saudi Arabia)	KM-RS16A1R	—
220V, 60Hz (for Taiwan)	KM-RS16A1T	—
110/115V, 60Hz	—	KM-RS34A1A
230/240V, 50Hz	—	KM-RS34A1E
220V, 50Hz/60Hz	—	KM-RS34A1K
220V, 50Hz/60Hz (for Saudi Arabia)	—	KM-RS34A1R
220V, 50Hz/60Hz (for Taiwan)	—	KM-RS34A1T
<b>External dimensions (W x D x H)*1</b>	800 x 465 x 1090 (mm) 31.5 x 18.3 x 42.9 (inch)	800 x 465 x 1800 (mm) 31.5 x 18.3 x 70.9 (inch)
<b>Internal dimensions (W x D x H)</b>	720 x 300 x 725 (mm) 28.3 x 11.8 x 28.5 (inch)	720 x 350 x 1435 (mm) 28.3 x 13.8 x 56.5 (inch)
<b>Effective capacity</b>	158 liters (5.6 cu.ft.)	340 liters (12.0 cu.ft.)
<b>Net weight</b>	71 kg (156 lbs.)	100 kg (220 lbs.)
<b>External cabinet</b>	Galvanised steel with baked-on finish	
<b>Internal cabinet</b>	Stainless steel	
<b>Insulation</b>	Polyurethane foam	
<b>Doors</b>	Sliding glass doors, double-glazing glass with heat-reflective film	
<b>Shelves</b>	Hard steel wire	
<b>Access port</b>	30mm $\phi$ on back wall	
<b>Lighting / Casters</b>	LED/2 casters	
<b>Compressor</b>	Hermetic type, 90 W	Hermetic type, 160 W
<b>Refrigerant</b>	HFC	
<b>Evaporator</b>	Fin & Tube, Forced-air circulation	
<b>Condenser</b>	Wire & Tube	
<b>Defrosting</b>	Cyclical defrosting & evaporator temp. detection system	
<b>Defrosting heaters</b>	87 W	101 W
<b>Temperature control</b>	2°C to 14°C	
<b>Temperature display</b>	Digital (1°C increments)	
<b>High/Low temperature alarm system</b>	$\pm 2^{\circ}\text{C}$ to $\pm 14^{\circ}\text{C}$ from temperature setting value	
<b>Door ajar alarm</b>	Buzzer / door ajar lamp	
<b>Options</b>	Temperature recorder: MTR-0621LH-PE/PA (recorder fixing: MPR-S30-PW) MTR-G04C-PE/G04A-PA (recorder fixing: MPR-S7-PW) Battery mounting box: KM-RPP01BB1W Interface board: MTR-480-PW, MTR-L03-PW DAQ system: MTR-5000-PW	


Caution: Panasonic guarantees the product under certain warranty conditions.

Panasonic in no way shall be responsible for any loss of content or damage to content.

• Appearance and specifications are subject to change without notice.

• Water condensation may sometimes appear on the glass doors, but this is normal and not a malfunction.

\*1 Exterior dimensions of main cabinet only - see dimension drawings showing handles and other external projections.



Panasonic Healthcare Co., Ltd., Medical Systems Business Unit is certified for:

**Quality management system: ISO9001**

**Medical devices quality management system: ISO13485**



Panasonic Healthcare Co., Ltd., Medical Systems Business Unit is certified for:

**Environmental management system: ISO14001**

DISTRIBUTED BY:

**Sheng Guan 聖川實業有限公司**

電話：02-2980-7936 傳真：02-8988-3071

地址：新北市三重區五華街1巷26號1樓

E-mail: service@sagevision.com.tw

**Panasonic**

<http://panasonic.net/healthcare/biomedical/>

Printed in Japan 192-2013-09